

LIQUID FILLABLE GAUGE



E-mail: sales@jilgauges.com

Tel.: +886-5-233-5069

L200L

Stainless steel housing
brass internals



Application

- pressure measurement of gaseous and liquid media that do not attack the copper alloy wetted parts
- outdoor and ambient conditions
- process systems
- compressors
- pumps
- oil field equipment
- pressure washers
- hydraulic equipment

Basic description

- stainless steel housing
- black finished aluminium pointer
- stainless steel crimp ring
- aluminium dial face
- phosphor bronze Bourdon tube
- sealing types: NPT, BSPP, and BSPT
- brass internals, socket, and connector
- custom designs are available upon request

Standard features

Optional features

Dia. sizes	40mm(1.5")	50mm(2")	63mm(2.5")	75mm(3")	100mm(4")
Range	Vacuum 4000 psi	Vacuum 8000 psi	Vacuum 8000 psi	Vacuum 8000 psi	Vacuum 8000 psi
Accuracy	± 2.5%	± 2.5%	± 1.6%	± 1.6%	± 1.0%

Dia. sizes	40mm(1.5")	50mm(2")	63mm(2.5")	75mm(3")	100mm(4")
Bottom	✓	✓	✓	✓	✓
Center Back	✓	✓	✓	✓	✓
Lower Back			✓	✓	✓