

LIQUID FILLABLE GAUGE



E-mail: sales@jilgauges.com

Tel.: +886-5-233-5069

L300L

Stainless steel housing
stainless steel
internals



Standard features



Application

- pressure measurement of gaseous and liquid media that do not attack the stainless steel (SS316) wetted parts
- outdoor and ambient conditions
- process systems
- oil field equipment
- compressors
- pressure washers
- pumps
- hydraulic equipment



Basic description

- stainless steel housing
- stainless steel crimp ring
- stainless steel (SS316) Bourdon tube
- stainless steel (SS304) internals, socket, and connector
- black finished aluminium pointer
- aluminium dial face
- sealing types: NPT, BSPP, and BSPT
- custom designs are available upon request

Optional features

Dia. sizes	40mm(1.5")	50mm(2")	63mm(2.5")	75mm(3")	100mm(4")
Range	Vacuum 4000 psi	Vacuum 10000 psi	Vacuum 15000 psi	Vacuum 15000 psi	Vacuum 15000 psi
Accuracy	± 2.5%	± 2.5%	± 1.6%	± 1.6%	± 1.0%

Dia. sizes	40mm(1.5")	50mm(2")	63mm(2.5")	75mm(3")	100mm(4")
Bottom	✓	✓	✓	✓	✓
Center Back	✓	✓	✓	✓	✓
Lower Back			✓	✓	✓