

LIQUID FILLABLE GAUGE



E-mail: sales@jilgauges.com

Tel.: +886-5-261-5755

L30SL

Stainless steel housing
Stainless steel
internals



Application

- pressure measurement of gaseous and liquid media that do not attack the copper alloy wetted parts
- outdoor and ambient conditions
- process systems
- oil field equipment
- compressors
- pressure washers
- pumps
- hydraulic equipment

Basic description

- stainless steel housing
- stainless steel **crimp** ring
- phosphor bronze Bourdon tube
- stainless steel internals
- with isolated connector
- aluminium dial face
- sealing types: NPT, BSPP, and BSPT
- custom designs are available upon request

Standard features

Optional features

Dia. sizes	40mm(1.5")	50mm(2")	63mm(2.5")	75mm(3")	100mm(4")
Range	Vacuum 6000 psi	Vacuum 8000 psi	Vacuum 8000 psi	Vacuum 8000 psi	Vacuum 8000 psi
Accuracy	± 2.5%	± 2.0%	± 1.6%	± 1.6%	± 1.0%

Dia. sizes	40mm(1.5")	50mm(2")	63mm(2.5")	75mm(3")	100mm(4")
Bottom	✓	✓	✓	✓	✓
Center Back	✓	✓	✓	✓	✓
Lower Back			✓	✓	✓