

# LIQUID FILLABLE GAUGE



E-mail: [sales@jilgauges.com](mailto:sales@jilgauges.com)

Tel.: +886-5-233-5069

## L320L

Stainless steel housing  
stainless steel  
internals



### Standard features



#### Application

- pressure measurement of gaseous and liquid media that do not attack the stainless steel (SS316) wetted parts
- outdoor and ambient conditions
- process systems
- oil field equipment
- compressors
- pressure washers
- pumps
- hydraulic equipment



#### Basic description

- stainless steel housing
- stainless steel **friction** ring
- stainless steel (SS316) Bourdon tube
- stainless steel (SS304) internals, socket, and connector
- black finished aluminium pointer
- aluminium dial face
- sealing types: NPT, BSPP, and BSPT
- custom designs are available upon request

### Optional features

Dia. sizes	40mm(1.5")	50mm(2")	63mm(2.5")	100mm(4")
Range	Vacuum 4000 psi	Vacuum 10000 psi	Vacuum 15000 psi	Vacuum 6000 psi
Accuracy	± 2.5%	± 2.5%	± 1.6%	± 1.0%

Dia. sizes	40mm(1.5")	50mm(2")	63mm(2.5")	100mm(4")
Bottom			✓	✓
Center Back			✓	
Lower Back			✓	✓