UTILITY GAUGE



E-mail: sales@jilgauges.com

Tel.: +886-5-233-5069





Application

- pressure measurement of liquid media that do not clog connection ports, or corrode copper alloy
- where rapid pressure fluctuation is expected
- compressors
- filters

regulators

- water pumps
- paint sprayers, and many more

Basic description

- black finished stainless steel housing
- black finished stainless steel ring
- glass/polycarbonate (PC) lens
- phosphor bronze Bourdon tube
- brass internals, socket, and connector
- black finished aluminium pointer
- aluminium dial face
- sealing types: NPT, BSPP, and BSPT
- custom designs are available upon request

Standard features

Optional features

| Dia. sizes | 40mm(1.5") | 50mm(2") | 63mm(2.5") | 75mm(3") | 100mm(4") | | | |
|--|--------------------|----------------------------|---------------------------|---------------------------|-------------------------|--|--|--|
| Range | Vacuum 4000 psi | Vacuum 10000 psi | Vacuum ≀ I 5000 psi | Vacuum 6000 psi | Vacuum { 6000 psi | | | |
| Accuracy | ± 2.5% | ± 2.5% | ± 2.0% | ± 1.6% | ± 1.6% | | | |
| Diameter sizes 150mm & 160mm are available | | | | | | | | |

| Dia. sizes | 40mm(1.5") | 50mm(2") | 63mm(2.5") | 75mm(3") | 100mm(4") |
|-------------|------------|----------|------------|------------|------------|
| Bottom | ✓. | <u> </u> | <u> </u> | | . / |
| Center Back | ✓. | √ | <u> </u> | . / | √ |